



Additional Dimensions: (Part # 451721)

- Exterior Projection is 2 7/8"
- Interior Projection Depends on Handle Style
- Overall Grip thickness: 1 1/16"
- Clearance between door & grip: 2"
- Standard Interior trim dimensions same as 7100 and 8474.
- Plates thickness: 1/2"

Same Dimensions for Dummy Function

Additional Dimensions: (Part # 451822/450923)

- Exterior Projection is 2 7/8"
- Interior Projection Depends on Handle Style
- Overall Grip thickness: 1 1/16"
- Clearance between door & grip: 1 1/2"
- Plates thickness: 1/2"

Same Dimensions for Dummy Function

Door Thickness Specifications - Sandcast Bronze Tubular Entrance Handlesets

Sandcast Bronze Tubular Entryset Sectional, Single Cylinder

Ridgemont (453727), Logan (453828)

<ul style="list-style-type: none"> • Standard Door Thickness: 1¹/₂" - 2" Standard Components: • 1¹/₂" & 2" Rosette Screws • Single Cylinder Tailpiece • Outside Entry Spindle • Inside Passage Half Spindle • 2¹/₂" Deadbolt Mounting Screws • Full-Lip Strike Plate • Deadbolt Strike Plate 	<ul style="list-style-type: none"> • Extended Door Thickness: 2" - 2¹/₂" Extended Components: • 2" Rosette Screws • Long Single Cylinder Tailpiece • Long Outside Entry Spindle • Long Inside Passage Half Spindle • 3" Deadbolt Mounting Screws • Spindle Extensions • Extended Full-Lip Strike Plate • Deadbolt Strike Plate 	<ul style="list-style-type: none"> • Extended Door Thickness*: 2¹/₂" - 2⁷/₈" Extended Components: • 2¹/₂" Rosette Screws • Extra Long Single Cylinder Tailpiece • Long Outside Entry Spindle • Extra Long Inside Passage Half Spindle • 3¹/₂" Deadbolt Mounting Screws • Spindle Extensions • Extended Full-Lip Strike Plate • Deadbolt Strike Plate • 3" Bottom Screw Required for Logan * 3" Bottom Screw for Ridgemont Style Available Upon Request
---	---	--

Sandcast Bronze Tubular Entryset Sectional, Double Cylinder

Ridgemont (454727), Logan (454828),

<ul style="list-style-type: none"> • Standard Door Thickness: 1³/₄" - 2" Standard Components: • 1¹/₂" Rosette Screws • Double Cylinder Tailpiece • Outside Entry Spindle • Inside Passage Half Spindle • 2¹/₂" Deadbolt Mounting Screws • 3" Deadbolt Screw for Logan • Full-Lip Strike Plate • Deadbolt Strike Plate 	<ul style="list-style-type: none"> • Extended Door Thickness: 2¹/₄" - 2⁵/₈" Extended Components: • 2" & 2¹/₂" Rosette Screws • Long Double Cylinder Tailpiece • Long Outside Entry Spindle • Long Inside Passage Half Spindle • 3" & 3¹/₂" Deadbolt Mounting Screws • Spindle Extensions • Extended Full-Lip Strike Plate • Deadbolt Strike Plate
---	--

Sandcast Bronze Tubular Full Length Entryset, Single Cylinder

Brighton (453929)

<ul style="list-style-type: none"> • Standard Door Thickness: 1¹/₂" - 2" Standard Components: • 1¹/₂" & 2" Rosette Screws • Single Cylinder Tailpiece • Outside Entry Spindle • Long Inside Passage Half Spindle • 2¹/₂" Deadbolt Mounting Screws • Full-Lip Strike Plate • Deadbolt Strike Plate 	<ul style="list-style-type: none"> • Extended Door Thickness: 2" - 2¹/₂" Extended Components: • 2" Rosette Screws • Long Single Cylinder Tailpiece • Long Outside Entry Spindle • Long Inside Passage Half Spindle • 3" Deadbolt Mounting Screws • Spindle Extensions • Extended Full-Lip Strike Plate • Deadbolt Strike Plate • 1 1/2" Screw for Mounting Plate 	<ul style="list-style-type: none"> • Extended Door Thickness: 2¹/₂" - 2⁷/₈" Extended Components: • 2¹/₂" Rosette Screws • Extra Long Single Cylinder Tailpiece • Long Outside Entry Spindle • Extra Long Inside Passage Half Spindle • 3¹/₂" Deadbolt Mounting Screws • Spindle Extensions • Extended Full-Lip Strike Plate • Deadbolt Strike Plate • 3" Bottom Screw Required
--	--	--

Sandcast Bronze Tubular Full Length Entryset, Double Cylinder

Brighton (454929)

<ul style="list-style-type: none"> • Standard Door Thickness: 1³/₄" - 2" Standard Components: • 1¹/₂" Rosette Screws • Double Cylinder Tailpiece • Outside Entry Spindle • Long Inside Passage Half Spindle • 2¹/₂" & 3" Deadbolt Mounting Screws • Full-Lip Strike Plate • Deadbolt Strike Plate 	<ul style="list-style-type: none"> • Extended Door Thickness: 2" - 2⁵/₈" Extended Components: • 2" & 2¹/₂" Rosette Screws • Long Double Cylinder Tailpiece • Long Outside Entry Spindle • Long Inside Passage Half Spindle • 3" & 3¹/₂" Deadbolt Mounting Screws • Spindle Extensions • Extended Full-Lip Strike Plate • Deadbolt Strike Plate
--	---

Ridgemont Trim

Logan Trim

Brighton Trim



**Single
Cylinder**

Part # 453727

Part # 453828

Part # 453929

**Double
Cylinder**

Part # 454727

Part # 454828

Part # 454929

Standard with Grip By Grip Handleset

- Standard 2 1/8" Door Prep
- Schlage C Keyway

Available Finishes: Flat Black (FB), Medium Bronze (MB)

Dimensions for **Grip-By-Grip Entrance** are the same as the Exterior Trim of standard grip handlesets.

Grip-By-Grip Tubular Entryset, Single Cylinder

Ridgemont (453727), Logan (453828), Brighton (453929)

<ul style="list-style-type: none"> • Standard Door Thickness: 1 5/8" - 2" Standard Components: • 1 1/2" & 2" Rosette Screws • Single Cylinder Tailpiece • Outside Entry Spindle • Inside Passage Half Spindle • For 1 5/8" thick door, use 2" Deadbolt Mounting Screws • For 2" thick door, use 2 1/2" Deadbolt Mounting Screws • Full-Lip Strike Plate • Deadbolt Strike Plate • 3" Screw For Grip 	<ul style="list-style-type: none"> • Extended Door Thickness: 2" - 2 1/2" Extended Components: • 2" & 2 1/2" Rosette Screws • Long Single Cylinder Tailpiece • Long Outside Entry Spindle • 3" Deadbolt Mounting Screws • Extended Full-Lip Strike Plate • Deadbolt Strike Plate • For 2 1/2" thick door, 3 1/2" Screw for Grip 	<ul style="list-style-type: none"> • Extended Door Thickness: 2 1/2" - 3" Extended Components: • 2 1/2" & 3" Rosette Screws • Extra Long Single Cylinder Tailpiece • Long Outside Entry Spindle • 3 1/2" Deadbolt Mounting Screws • Extended Full-Lip Strike Plate • Deadbolt Strike Plate • Need Longer Screws For Grip and Housing • Includes 3 1/2" Screw for Grip
--	---	--

Grip-By-Grip Tubular Entryset, Double Cylinder

Ridgemont (454727), Logan (454828), Brighton (454929)

<ul style="list-style-type: none"> • Standard Door Thickness: 1 5/8" - 2 1/8" Standard Components: • 1 1/2" Rosette Screws • Double Cylinder Tailpiece • Outside Entry Spindle • 2 1/2" & 3" Deadbolt Mounting Screws • Full-Lip Strike Plate • Deadbolt Strike Plate • Include 3" Screw for Grip 	<ul style="list-style-type: none"> • Extended Door Thickness: 2 1/8" - 3" Extended Components: • 3" Rosette Screws • For 2 1/8" thick door, use 2" Screw for Rosette • Long Double Cylinder Tailpiece • Long Outside Entry Spindle • 3" & 3 1/2" Deadbolt Mounting Screws • Extended Full-Lip Strike Plate • Deadbolt Strike Plate • Include 3" and 3 1/2" Screw for Grip
--	--

Face and Strike Plates

Deadbolt Strike Plates

